

## 高温热电偶

# High Temperature Thermocouple

### 1、应用

适用于各种生产过程中高温场合，广泛应用于玻璃及陶瓷及工业盐浴炉等测温。

### 2、主要技术参数

电气出口：M20x1.5,NPT1/2

精度等级：I、II

防护等级：IP65

偶丝直径：Φ0.5

公称压力：常压

### 3、型号及规格

### 1、Application

It is suitable for all kinds of high temperature circumstance in the process of production, are widely used in temperature measurement in glass and ceramic, industrial salt bath furnace, etc

### 2、Main technical parameters

Electrical outlet: M20x1.5,NPT1/2

Accuracy class: I、II

Protection class: IP65

O.D of thermocouple wire: Φ0.5

PN: normal pressures

### 3、Model and specification

型号 model	分度号 degree	测温范围℃ Temperature range °C	保护管材料 material of thermowell	响应时间 response time	规格 specification	
					d	LxI
WRP-130 WRP2-130	S	0-1300	高铝质 high alumina	< 150S	Φ16	300x150
WRP-131 WRP2-131				< 360S	Φ25	350x200
WRQ-130 WRQ2-130	R	0-1300		< 150S	Φ16	400x250
WRQ-131 WRQ2-131				< 360S	Φ25	450x300
						550x400
WRR-130 WRR2-130	B	0-1600		刚玉管 corundum tube	< 150S	Φ16
WRR-131 WRR2-131			< 360S		Φ25	900x750
			< 150S		Φ16	1150x1000
			< 360S		Φ25	1650x1500
						2150x2000